



By order No. 1104 To me
dictated by Emosh Fuller
Clerk of Monroe Circuit Court
to locate and establish the
North line of Section 18. Town
7 North Range 1 West and the
North East North West and
the 1/2 Mile corners there on.

After interested parties
having been duly and
legally notified, did proceed
on the 25, 26, & 27. days
of October A.D. 1887 to
locate said line and
establish said corners as
directed.

By beginning at a stone for
1/2 Mile past on the East
of Section 7 & 7 N. R. 1. W.
(much original wit standing)

Ran South 80.00 lbs to stone for 1/2
Mile past on East of Sec 18. Came
out at point 24 lbs. South & 2 1/2 lbs
East of Stone for 1/2 m. past.
Located "A" (North East Cor. of
Section 18) at average dist. line
run. For Corner set lime stone
marked S. 7. 8. 17. 18.
Thence Ran West recorded dist
for North line of Sec 18. drove stake

Then began at the South West
Corner of Sec 18 Ran North on

Range line Recorded distances for west lines
of Sections 7 & 18 to the North West Cor. of Sec 7
Came out at point 88 lbs South & 26 lbs East
of Cor. Thence Corrected line. & Established
(B) North West Cor. of Sec 18.

- A N. Corner Sec 18 { W Walnut 5539 E 27
Set lime stone. Hickory 3521 E 9
- B N.W. cor Sec 18 { B Walnut 4 213 1/2 E 52
Set lime stone Poplar 8 287 1/2 W 87
- C 1/2 M on North { B Walnut 10523 E 47
Set lime stone Sugar 10 285 W 110
- D 1/2 M on E { B Walnut 12 25 1/2 E 78
made new int